Designer

Design year



Pressalit 2000 124 Standard toilet seat incl. hinge in stainless steel

Pressalit

1991

Item number	124000-B13999 EAN:5708590075518	
	The cover on the Pressalit 2000 is smaller than the ring seat, giving it a light and elegant design.	
Colour	White	
Description	PRESSALIT toilet seat with cover, model "2000", art. no. 124 made of colour ingrained duroplast with UN3 univertical hinge of stainless steel alternative hinges: B13, DO7, UN4, BV7 and BV5 - centre distance: 120 - 170 mm - load - ring seat 240 kg - suitable for many universal toilets - also with institutional hinges on request (project seat) - 10 year guarantee	
	120 - 170 A7222/A7223/ A7236 A7153 A7203 A7203 A7118 A7022 A7050	A4003 A4001 A7236 A9108
Design type	Sandwich	



Pressalit 2000 124 Standard toilet seat incl. hinge in stainless steel

Material

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

HINGE LINKS:

Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85. Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.

MOUNT/HINGES:

Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85. Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.

Weight (kg) 2.59

Carton size 463x391x69 mm

Gross weight (kg) 2.89

Colli size 472x400x348 mm

Colli weight (kg) 14.45

Qty per colli 5

Colli per pallet 18

Qty per pallet 90

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.





Pressalit 2000 124 Standard toilet seat incl. hinge in stainless steel

Warranty

Pressalit provides a 10-year product warranty on your toilet seat. Pressalit will repair or exchange the toilet seat for the same or another useable model, at Pressalit's discretion, in the event of a material or manufacturing defect in your toilet seat appearing within 10 years of the date of purchase with normal use. This product warranty is conditional upon proof of purchase of the toilet seat.

Subject to changes in the product range, technical changes and printing errors.





www.pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com PRESSALIT.