





Pressalit 2000 124
Standard toilet seat incl. hinge in stainless steel

Item number	124000-UN3999 EAN:5708590299075	
Colour	White	
Description	<p>PRESSALIT toilet seat with cover, model "2000", art. no. 124 made of colour ingrained duroplast with UN3 univertical hinge of stainless steel.</p> <ul style="list-style-type: none"> - alternative hinges: B13, DO7, UN4, BV7 and BV5 - centre distance: 120 - 170 mm - load - ring seat 240 kg - suitable for many universal toilets - also with institutional hinges on request (project seat) - 10 year guarantee 	
	  	
Design type	Sandwich	
Designer	Pressalit	
Design year	1991	

Pressalit 2000 124
Standard toilet seat incl. hinge in stainless steel

Material	<p>TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.</p> <p>BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).</p> <p>HINGE LINKS: Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85. Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.</p> <p>MOUNT/HINGES: Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85. Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.</p>
Weight (kg)	2.6069
Carton size	463x391x69 mm
Gross weight (kg)	2.9069
Colli size	472x400x348 mm
Colli weight (kg)	14.5345
Qty per colli	5
Colli per pallet	18
Qty per pallet	90
Cleaning	<p>Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.</p>

Pressalit 2000 124
Standard toilet seat incl. hinge in stainless steel

Warranty

Pressalit provides a 10-year product warranty on your toilet seat. Pressalit will repair or exchange the toilet seat for the same or another useable model, at Pressalit's discretion, in the event of a material or manufacturing defect in your toilet seat appearing within 10 years of the date of purchase with normal use. This product warranty is conditional upon proof of purchase of the toilet seat.

Subject to changes in the product range, technical changes and printing errors.



www.pressalit.com
