

## Pressalit 1000 304 Standard toilet seat incl. fixed hinge in stainless steel


304000-BG4999 Item number EAN:5708590189697


Pressalit 1000 is a universal toilet seat in excellent quality and particularly suited to building projects.


Colour White

**Description** PRESSALIT toilet seat with cover, model "1000", art. no. 304 made of colour ingrained duroplast with BG4 fixed hinge of stainless steel

- centre distance: 155 mm
- load ring seat 240 kg
- suitable for many universal toilets10 year guarantee







**Design type** 

Sandwich

Designer

Pressalit

Design year

2001



## Pressalit 1000 304 Standard toilet seat incl. fixed hinge in stainless steel

# Material TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

#### **BUFFERS**:

EVA (copolymer made of ethylene and vinyl acetate).

#### HINGE LINKS:

Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85. Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.

### MOUNT/HINGES:

Stainless steel (V2A) model W. no. 1.4301/M in accordance with DIN 17441/85. Composition: chrome (cr) 17-19%, nickel (ni) 8-11%, carbon <0.05%, molybdenum, manganese, silicone, sulphur, titanium.

Weight (kg) 2.2416

Carton size 465x391x68 mm

Gross weight (kg) 2.6416

**Colli size** 486x404x353 mm

Colli weight (kg) 13.208

Qty per colli 5

Colli per pallet 18

Qty per pallet 90

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.





Pressalit 1000 304 Standard toilet seat incl. fixed hinge in stainless steel

## Warranty

Pressalit provides a 10-year product warranty on your toilet seat. Pressalit will repair or exchange the toilet seat for the same or another useable model, at Pressalit's discretion, in the event of a material or manufacturing defect in your toilet seat appearing within 10 years of the date of purchase with normal use. This product warranty is conditional upon proof of purchase of the toilet seat.

Subject to changes in the product range, technical changes and printing errors.





www.pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

